

CLAIMS

The following is claimed:

- 1 1. A method of generating a boundary-scan description language file for
2 an integrated circuit; comprising the steps of:
3 creating a flat netlist that describes said integrated circuit, wherein said flat
4 netlist comprises connectivity information regarding leaf cells within said integrated
5 circuit;
6 determining and storing a name provided for each joint test action group
7 register located within said integrated circuit, from said created flat netlist;
8 determining relationships between each joint test action group register located
9 within said integrated circuit and at least one input/output pin located within said
10 integrated circuit, from said created flat netlist, and storing a description of said
11 relationships; and
12 creating said boundary-scan description language file from said stored names
13 of each joint test action group and said stored description of said relationship between
14 said joint test action group register and said input/output pin.

1 2. The method of claim 1, wherein said step of creating a flat netlist
2 further comprises the steps of:
3 traversing at least one hierarchical netlist that describes portions of said
4 integrated circuit, for at least one individual netlist that describes a logic portion of
5 said integrated circuit; and
6 combining connectivity information provided by said at least one individual
7 netlist, resulting in said flat netlist.

1 3. The method of claim 2, wherein said connectivity information
2 comprises relationships between wires within said integrated circuit, said leaf cells
3 located within said integrated circuit and input/output pins.

1 4. The method of claim 2, wherein said joint test action group register
2 names are stored in the same order discovered during said traversing step.

1 5. The method of claim 2, further comprising the step of:
2 traversing said at least one hierarchical netlist for at least one individual netlist
3 that describes at least one pad located within said integrated circuit.

1 6. The method of claim 5, wherein said step of traversing said at least
2 one hierarchical netlist is started at a beginning of a boundary-scan line, and wherein
3 said step of traversing is ended at an end of said boundary-scan line.

1 7. The method of claim 1, wherein said joint test action group registers
2 comprise a JO joint test action group register, a JT joint test action group register, and
3 a JI joint test action group register.

1 8. A system for generating a boundary-scan description language file for
2 an integrated circuit, comprising:

3 means for creating a flat netlist that describes said integrated circuit, wherein
4 said flat netlist comprises connectivity information regarding leaf cells within said
5 integrated circuit;

6 means for determining and storing a name provided for each joint test action
7 group register located within said integrated circuit, from said created flat netlist;

8 means for determining relationships between each joint test action group
9 register located within said integrated circuit and at least one input/output pin located
10 within said integrated circuit, from said created flat netlist, and for storing a
11 description of said relationships; and

12 means for creating said boundary-scan description language file from said
13 stored names of each joint test action group and said stored description of said
14 relationship between said joint test action group register and said input/output pin.

1 9. The system of claim 8, further comprising:

2 means for traversing at least one hierarchical netlist that describes portions of
3 said integrated circuit, for at least one individual netlist that describes a logic portion
4 of said integrated circuit; and

5 means for combining connectivity information provided by said at least one
6 individual netlist, resulting in said flat netlist.

10079337-022002

1 14. The system of claim 8, wherein said joint test action group registers
2 comprise a JO joint test action group register, a JT joint test action group register, and
3 a JI joint test action group register.

1 15. A system for generating a boundary-scan description language file for
2 an integrated circuit, comprising:
3 a memory;
4 software stored within said memory defining functions to be performed by
5 said system; and
6 a processor configured by said software to perform the steps of:
7 creating a flat netlist that describes said integrated circuit, wherein said
8 flat netlist comprises connectivity information regarding leaf cells within said
9 integrated circuit;
10 determining and storing a name provided for each joint test action
11 group register located within said integrated circuit, from said created flat netlist;
12 determining relationships between each joint test action group register
13 located within said integrated circuit and at least one input/output pin located within
14 said integrated circuit, from said created flat netlist, and storing a description of said
15 relationships; and
16 creating said boundary-scan description language file from said stored
17 names of each joint test action group and said stored description of said relationship
18 between said joint test action group register and said input/output pin.

1 16. The system of claim 15, wherein said step of creating a flat netlist
2 further comprises the steps of said processor traversing at least one hierarchical netlist
3 that describes portions of said integrated circuit, for at least one individual netlist that
4 describes a logic portion of said integrated circuit, and said processor combining
5 connectivity information provided by said at least one individual netlist, resulting in
6 said flat netlist.

1 17. The system of claim 16, wherein said connectivity information
2 comprises relationships between wires within said integrated circuit, said leaf cells
3 located within said integrated circuit and input/output pins.

1 18. The system of claim 16, wherein said joint test action group register
2 names are stored in the same order discovered during said traversing step.

1 19. The system of claim 16, wherein said processor is further configured
2 by said memory to perform the step of traversing said at least one hierarchical netlist
3 for at least one individual netlist that describes at least one pad located within said
4 integrated circuit.

1 20. The system of claim 19, wherein said step of traversing said at least
2 one hierarchical netlist is started at a beginning of a boundary-scan line, and wherein
3 said step of traversing is ended at an end of said boundary-scan line.